

# Drylok™

The industry's driest, safest disconnect

# Kamvalok®

Automatic flow interruption, cam-and-groove simplicity



## OPW Dry Disconnect Couplings

Your guide to the industry's most complete line of dry disconnects

### Drylok

- Less than 1-cc of fluid loss from 3" unit upon disconnect
- Interlocking handle prevents uncoupling during fluid transfer
- Operates at higher pressures, flow rates, and viscosities... rated 300 psi open, 150 psi closed
- Easy, foolproof operation



Drylok 5700-Series  
Coupler with dust plug

**Ordering Chart** Call OPW Customer Service at 800-547-9393 for complete ordering information

#### O-Ring Seal

- B - Viton-B
- C - Viton-E
- E - EPDM
- F - Teflon®
- Encapsulated Viton-A
- N - Buna-N
- T - Teflon
- Encapsulated Silicone
- V - Viton-A
- W - White Nitrile
- Y - Kalrez® (4079)
- Z - Kalrez (6375)

#### Construction Material

- 6 - Aluminum
- 7 - 316 Stainless Steel
- 8 - Alloy 20®

#### Style

- A - ANSI Flange 150 Lbs
- B - Female BPT
- C - Cutaway
- D - Din Flange
- N - Female NPT
- P - Sanitary Triclam
- T - ANSI Flange 300 Lbs
- W - Butt Weld
- X - Parking Adaptor

## 5670-V720N

#### Type

- 56 - Adaptor
- 57 - Coupler

#### Size

- 10 - 1"
- 20 - 2"
- 30 - 3"

Drylok 5600-Series  
Adaptor with dust cap



### Kamvalok

- Automatically stops fluid flow during accidental uncoupling
- Cam-and-groove operation for economy and convenience
- The original dry disconnect... proven in thousands of installations

**Ordering Chart** Call OPW Customer Service at 800-547-9393 for complete ordering information

#### Series

- 16 - Kamvalok Adaptor
- 17 - Kamvalok Coupler
- 22 - D2000 Coupler

#### Configure

- 1 - Aluminum Body, Plated Steel & Delrin Internals (Coupler)
- Aluminum Body, Stainless Steel Internals (Adaptor)
- 6 - Aluminum Body, Stainless Steel Internals (Coupler)
- 7 - Stainless Steel Body, Stainless Steel Internals (Coupler/Adaptor)

#### Size

- 15 - 1-1/2" FNPT
- 20 - 2" FNPT
- 30 - 3" FNPT

## 1611AN - AL15 - GL

#### O-Ring Seal

- 1 - Buna-N
- 2 - Viton®-A
- 3 - TFE/Silicone Core/Chemraz
- 4 - EPT
- 6 - Chemraz
- 7 - TFE/Viton Core
- 9 - Viton-B

#### Type

- AN - Adaptor
- D - Coupler

#### Construction Material

- AL - Aluminum Body
- SS - Stainless Steel Body

#### Style

- A - 150 Lb. Flange
- GL - Greaseless
- KG - Krytox Grease
- KL - Keylok
- P - Sanitary Triclam
- T - 300 Lb. Flange



1700 D Series Coupler



1700 ES Series Coupler

1700 D Series Coupler  
with optional locking handle



1600 ANF Series Adaptor  
150 Lb. ANSI Flange



1600 ANFT Series Adaptor  
300 Lb. ANSI Flange

1672 AN Adaptor



1673 AN Adaptor



#### D2000 Actuator Series

*When automatic shut-off is not required*

- Ideal for vapor recovery or suction pump applications
- Locking handle and simple cam-and-groove operation
- Compatible with Kamvalok adaptors

634 B Dust Plug



734 A Dust Cap

733 DCL Dust Cap

513-696-1500

**OPW® Engineered Systems**

800-547-9393

Web site: [www.opw-es.com](http://www.opw-es.com)

Drylok is a trademark, and Kamvalok and OPW are registered trademarks of OPW Engineered Systems. OPW Engineered Systems holds various patents on Drylok and Kamvalok Dry Disconnect Couplings.

© Copyright 2005 OPW All rights reserved DRYDPOSTER Printed in U.S.A.

A Dover Company